VILLAGE OF SLINGER WASHINGTON COUNTY, WISCONSIN

APPLICATION FOR ROAD ACCESS/DRIVEWAY PERMIT

The Undersigned hereby applies for a road access permit in the Village of Slinger.	For Office Use Only	:
The Undersign agrees that all work shall be done as shown on the Location Sketch hereof, in accordance with the requirements of the laws and regulations of the State of Wisconsin, the Village Zoning Ordinance, and all other applicable Village Ordinances.		By:
	Sized By:	
Owner of Site		
Address	Address of Premise Affected	
City, State, Zip	Subdivision	Lot#
()() Phone Fax	Zoning Classification	
Proposed Access should be staked	Tax Key #	
with an orange flag and located in the center of the area requesting approval.	Section #	
	Signature Required	Date

Limitations and Standards:

- 1.) No access to a roadway shall be permitted within 100' of the intersection of the right-of-way lines of an arterial street intersecting with another arterial street, within 50' of the intersection of the right-of-way lines of any other street intersecting with an arterial street.
- 2.) In acting upon applications for access permits the Village Engineer shall determine whether the proposed access location is consistent with public safety, sound planning principles and the logical extension of roads and public services.
- 3.) Culvert Size. All culverts, drain pipes, or other similar conduits placed on, in and along the public right-of-way of a Village street shall be sized and approved by the Village Engineer, and shall be of sufficient length so as to prevent injury to persons or property in the use of the roadways or the entrances to or exists from the roadways over across such culverts provided that no culvert shall be less than twenty (20) feet nor more than thirty-five (35) feet in length. End culvert pieces or sections, when required, shall be the type designated by the Village Engineer.

4.) Any and all other requirements as defined in Section 8.10 of the Village of Slinger's Code of Ordinances.

5.) DRIVEWAYS

All driveways installed, altered, changed, replaced, or extended after the effective date of this ordinance shall meet the following requirements:

A. Driveway Islands

Islands between driveway openings shall be provided with a minimum of six (6) feet between all driveways and three (3) feet at all lot lines;

B. <u>Driveway Openings</u>

Driveway openings for vehicular ingress and egress shall not exceed twenty-four feet (24') at the right-of-way line and roadway in residential districts; and shall not exceed thirty feet (30') at the right-of-way line and thirty-five feet (35') at the roadway in all other districts;

C. Ingress/Egress

Ingress/Egress to drive-in banks, motels, funeral homes, vehicular sales, service, washing and repair stations or garages shall be not less than two hundred feet (200') from any pedestrian entrance or exit to a school, college university, church, hospital, park, playground, library, public emergency shelter, or other place of pubic assembly.

D. <u>Driveway Aprons</u>

The area between curb and sidewalk must be seven (7) inches of concrete.